

Sizes Sizes	31.5x57 cm 12 3/8"x22 1/2" ± 9mm	
----------------	--	--

TECHNICAL FEATURES / TECHNICAL FEATURES			Requirements for nominal size N			WARP WALL
			Requirements for nominal size N			
			7 cm ≤ N < 15 cm		N ≥ 15 cm	
			(mm)	(%)	(mm)	
e.c. + 0,75 - 0,50	e.c. + 0,5 - 0,3	e.c. + 2,0 - 1,5				
w. ± 0,75	w. ± 0,5	w. ± 2,0				
			EN 14411 annex L (Group BIII) EN 14411 annex L (Group BIII)	ISO 13006 annex L (Group BIII) ISO 13006 annex L (Group BIII)		

(*) The permissible deviation, in % or mm, of the average size for each tile (2 or 4 sides) from work size (W).

(**) The permissible deviation, in % or mm, of the average thickness for each tile from the work size thickness (W).

(***) The maximum permissible deviation from straightness, in % or mm, related to the corresponding work sizes (W).

(****) The maximum permissible deviation from rectangularity, in % or mm, related to the corresponding work sizes (W).

c.c. The maximum permissible deviation from centre curvature, in % or mm, related to diagonal calculated from the work sizes (W).

e.c. The maximum permissible deviation from edge curvature, in % or mm, related to the corresponding work sizes (W).

w The maximum permissible deviation from warpage, in % or mm, related to diagonal calculated from the work sizes (W).

(1) Requirements european standard EN 176.

(2) Determination of slip resistance of pedestrian surfaces; it does not cover sports surfaces and road surfaces for vehicles (skid resistance).

Anti-slip performance is guaranteed at the time of delivery of the product

